

Printing date 28.02.2023

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 3 (replaces version 2)

Revision: 28.02.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: Mipa WBC 2K-Decklack glänzend

- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- Application of the substance / the mixture Paint
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com
- 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word Warning

• Hazard-determining components of labelling: Reaction mass of pentamethyl-piperidyl sebacate C(M)IT/MIT (3:1)

Benzotriazole derivate

2,4,7,9-tetramethyldec-5-yne-4,7-diol

- Hazard statements
- H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P273 Avoid release to the environment.
- P280 Wear protective gloves.

P362+P364 Take off contaminated clothing and wash it before reuse.

- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P321 Specific treatment (see on this label).

(Contd. on page 2)

⁻ GB



according to 1907/2006/EC, Article 31

Revision: 28.02.2023

Printing date 28.02.2023

Version number 3 (replaces version 2)

Trade name: Mipa WBC 2K-Decklack glänzend

(Contd. of page 1)

· 2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	2.5-<10%
2-Butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg	<2.5%
2-dimethylaminoethanol Flam. Liq. 3, H226; Acute Tox. 3, H331; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335:C ≥ 5 %	<1%
Benzotriazole derivate Aquatic Chronic 2, H411; () Skin Sens. 1, H317	<i>≥</i> 0.25-<1%
Reaction mass of pentamethyl-piperidyl sebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Akin Sens. 1A, H317	≥0.1-<0.25%
2,4,7,9-tetramethyldec-5-yne-4,7-diol ♦ Eye Dam. 1, H318; ↑ Skin Sens. 1B, H317; Aquatic Chronic 3, H412	<i>≥</i> 0.1-<1%
C(M)IT/MIT (3:1)	≥0.00025-<0.0015%
	substance with a Community workplace exposure limit 2-Butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg 2-dimethylaminoethanol Flam. Liq. 3, H226; Acute Tox. 3, H331; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: $C \ge 5$ % Benzotriazole derivate Aquatic Chronic 2, H411; Skin Sens. 1, H317 Reaction mass of pentamethyl-piperidyl sebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317 2,4,7,9-tetramethyldec-5-yne-4,7-diol Eye Dam. 1, H318; Skin Sens. 1B, H317; Aquatic Chronic 3, H412 C(M)IT/MIT (3:1) Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C;H314: $C \ge 0.6$ % Skin Irrit. 2; H315: 0.06 % $\le C < 0.6$ % Eye Dam. 1; H318: $C \ge 0.6$ %

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31 Version number 3 (replaces version 2)

Revision: 28.02.2023

Trade name: Mipa WBC 2K-Decklack glänzend

(Contd. of page 2)

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately rinse with water.

After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Store away from foodstuffs.

· Further information about storage conditions: Protect from frost.

· Storage class: 12

· 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)



Printing date 28.02.2023



Printing date 28.02.2023

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 3 (replaces version 2)

Revision: 28.02.2023

Trade name: Mipa WBC 2K-Decklack glänzend

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

34590-94-8 Dipropylene glycol monomethyl ether

WEL Long-term value: 308 mg/m³, 50 ppm Sk

111-76-2 2-Butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV

108-01-0 2-dimethylaminoethanol

WEL Short-term value: 22 mg/m³, 6 ppm Long-term value: 7.4 mg/m³, 2 ppm

Ingredients with biological limit values:

111-76-2 2-Butoxyethanol

BMGV 240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid

Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB



Printing date 28.02.2023

Safety data sheet according to 1907/2006/EC, Article 31

Version number 3 (replaces version 2)

Revision: 28.02.2023

(Contd. of page 4)

Trade name: Mipa WBC 2K-Decklack glänzend

 \cdot Eye/face protection Goggles recommended during refilling

9.1 Information on basic physical and chen	nical properties	
General Information		
Physical state	Fluid	
Colour:	According to product specification	
Odour:	Characteristic	
Odour threshold:	Not determined.	
Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and		
boiling range	100 °C (7732-18-5 water, distilled, conductivity o	
	of similar purity)	
Flammability	Not applicable.	
Lower and upper explosion limit		
Lower:	Not determined.	
Upper:	Not determined.	
Flash point:	Not applicable.	
Ignition temperature:	207 °C (DIN 51794)	
Decomposition temperature:	Not determined.	
рН	Not determined.	
, Viscosity:		
Kinematic viscosity at 20 °C	45-55 s (DIN 53211/4)	
Dynamic:	Not determined.	
Solubility		
water:	Fully miscible.	
Partition coefficient n-octanol/water (log	·	
value)	Not determined.	
Vapour pressure at 20 °C:	23 hPa (7732-18-5 water, distilled, conductivity of of similar purity)	
Density and/or relative density		
Density at 20 °C:	1.034 g/cm³ (DIN EN ISO 2811-1)	
Relative density	Not determined.	
Vapour density	Not determined.	
9.2 Other information		
Appearance:		
Appearance. Form:	Fluid	
ronn: Important information on protection of hea		
and environment, and on safety.		
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not semigrituing. Product does not present an explosion hazard.	
Solvent content:	r roudel does not present an explosion nazaru.	
Water:	60.2 %	
	5.56 %	
VOC (EC)	5.50 % 34.2 %	
Solids content (weight-%):	JT.2 /0	
Change in condition Evaporation rate	Not determined.	
Information with regard to physical haza	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
AEIUSUIS		



according to 1907/2006/EC, Article 31 Version number 3 (replaces version 2)

Revision: 28.02.2023

Printing date 28.02.2023

Trade name: Mipa WBC 2K-Decklack glänzend	
---	--

		(Contd. of page 5
Gases under pressure	Void	
· Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- 11.2 Information on other hazards

· Endocrine disrupting properties

556-67-2 octamethylcyclotetrasiloxane

List II, III

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Remark: Harmful to fish

(Contd. on page 7)

GB

according to 1907/2006/EC, Article 31

Professional Coating Systems Printing date 28.02.2023

Version number 3 (replaces version 2)

Revision: 28.02.2023

Trade name: Mipa WBC 2K-Decklack glänzend

(Contd. of page 6)

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product. • **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

 · 14.1 UN number or ID number · ADR, ADN, IMDG, IATA 	Void
 14.2 UN proper shipping name ADR, ADN, IMDG, IATA 	Void
 14.3 Transport hazard class(es) 	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
 14.7 Maritime transport in bulk according a IMO instruments 	to Not applicable.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:

 Class
 Share in %

 NK
 2.5-<10</td>

(Contd. on page 8)

GB



according to 1907/2006/EC, Article 31

Printing date 28.02.2023

Version number 3 (replaces version 2)

Revision: 28.02.2023

Trade name: Mipa WBC 2K-Decklack glänzend

(Contd. of page 7)

• **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 3: Acute toxicity - Category 3 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Corr. 1C: Skin corrosion/irritation - Category 1C Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Skin Sens. 1B: Skin sensitisation – Category 1B Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 * * Data compared to the previous version altered.