

according to UK REACH

Printing date 19.08.2024 Version number 9 (r

Version number 9 (replaces version 8) Revision: 19.08.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: Mipa Winner-Spray Felgensilber
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Color spray
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Acetone

n-Butyl acetate

2-Methoxy-1-methylethyl acetate

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)



according to UK REACH

Printing date 19.08.2024 Version number 9 (replaces version 8) Revision: 19.08.2024

Trade name: Mipa Winner-Spray Felgensilber

(Contd. of page 1)

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone	25-50%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	Dimethyl ether § Flam. Gas 1A, H220; Press. Gas (Liq.), H280	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21	Propane Propane Flam. Gas 1A, H220; Press. Gas (Liq.), H280	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31	Butane, pure The pure state of the pure state o	2.5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate § Flam. Liq. 3, H226; (1) STOT SE 3, H336, EUH066	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Triangle Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	Isobutane State Isobutane	2.5-<10%
CAS: 9004-70-0	Nitrocellulose, nitrogen content <12,6% ♦ Expl. 1.1, H201	2.5-<10%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	Ethanol ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	<2.5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♠ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%

(Contd. on page 3)



according to UK REACH

Printing date 19.08.2024 Version number 9 (replaces version 8) Revision: 19.08.2024

Trade name: Mipa Winner-Spray Felgensilber

(Contd. of page 2)

CAS: 7429-90-5 aluminium powder (stabilized)/ manufacturer <2.5% EINECS: 231-072-3 classification

Reg.nr.: 01-2119529243-45 🚯 Flam. Sol. 1, H228

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

(Contd. on page 4)



according to UK REACH

Printing date 19.08.2024 Version number 9 (replaces version 8) Revision: 19.08.2024

Trade name: Mipa Winner-Spray Felgensilber

(Contd. of page 3)

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Do not seal receptacle gas tight.

BMGV 650 mmol/mol creatinine Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

Keep container tightly sealed.

- Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection	SECTION 8: Ex	posure controls	/personal	protection
--	---------------	-----------------	-----------	------------

Ingre	edients with limit values that require monitoring at the workplace:
67-64	1-1 Acetone
WEL	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm
115-1	10-6 Dimethyl ether
WEL	Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm
106-9	77-8 Butane, pure
WEL	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
123-8	86-4 n-Butyl acetate
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
108-6	55-6 2-Methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk
64-17	7-5 Ethanol
WEL	Long-term value: 1920 mg/m³, 1000 ppm
1330-	-20-7 Xylene
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
7429-	-90-5 aluminium powder (stabilized)/ manufacturer classification
WEL	Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust
	dients with biological limit values:

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)



according to UK REACH

Printing date 19.08.2024 Version number 9 (replaces version 8) Revision: 19.08.2024

Trade name: Mipa Winner-Spray Felgensilber

(Contd. of page 4)

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range -44.5 °C · Flammability Not applicable.

(Contd. on page 6)



according to UK REACH

Revision: 19.08.2024 Printing date 19.08.2024 Version number 9 (replaces version 8)

Trade name: Mipa Winner-Spray Felgensilber

(Contd. of page 5)

· Lower and upper explosion limit

1.7 Vol % (74-98-6 Propane) · Lower:

· Upper: 18.6 Vol % (115-10-6 Dimethyl ether)

<0 °C (DIN 53213) · Flash point:

Auto-ignition temperature: 235 °C (DIN 51794, 115-10-6 Dimethyl ether)

Decomposition temperature: Not determined. Not determined. · pH

· Viscosity:

Kinematic viscosity Not determined. · Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

Not determined. value)

· Vapour pressure at 20 °C: 8,300 hPa (74-98-6 Propane)

· Vapour pressure at 50 °C: 800 hPa

· Density and/or relative density

· Density at 20 °C: 0.743 g/cm3 (DIN 53217)

· Relative density Not determined. Not determined. · Vapour density

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 92.60 % · Solids content (weight-%): 7.4 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void

Extremely flammable aerosol. Pressurised · Aerosols

container: May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

· Substances and mixtures, which emit

flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void Corrosive to metals Void

(Contd. on page 7)



according to UK REACH

Printing date 19.08.2024 Version number 9 (replaces version 8) Revision: 19.08.2024

Trade name: Mipa Winner-Spray Felgensilber

(Contd. of page 6)

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)



Safety data sheet according to UK REACH

Printing date 19.08.2024 Version number 9 (replaces version 8) Revision: 19.08.2024

Trade name: Mipa Winner-Spray Felgensilber

(Contd. of page 7)

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informati	1011
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	2 5F Gases.
· Label	2.1
· Class · Label	2.1 Gases. 2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler c	Warning: Gases.
· EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capac of 1 litre: Category A. For AEROSOLS with capacity above 1 litre: Category B. For WAS AEROSOLS: Category C, Clear of living quarters
· Segregation Code	SG69 For AEROSOLS with a maximum capac of 1 litre: Segregation as for class 9. Stow "separated fro class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision



according to UK REACH

Printing date 19.08.2024 Version number 9 (replaces version 8) Revision: 19.08.2024

Trade name: Mipa Winner-Spray Felgensilber

(Contd. of page
ording to Not applicable.
1L
2
D
1L
UN 1950 AEROSOLS, 2.1
•

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

i disdiis Act	
· Regulated explosives precursors	
None of the ingredients is listed.	
· Regulated poisons	
None of the ingredients is listed.	
· Reportable explosives precursors	
67-64-1 Acetone	Listed

Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

7429-90-5 aluminium powder (stabilized)/ manufacturer classification

- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H201 Explosive; mass explosion hazard.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H280 Contains gas under pressure; may explode if heated.

(Contd. on page 10)

Listed



according to UK REACH

Revision: 19.08.2024 Printing date 19.08.2024 Version number 9 (replaces version 8)

Trade name: Mipa Winner-Spray Felgensilber

(Contd. of page 9)

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives - Division 1.1

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Press. Gas (Liq.): Gases under pressure - Liquefied gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Flam. Sol. 1: Flammable solids - Category 1

Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

^{* *} Data compared to the previous version altered.