

Safety data sheet according to UK REACH

Printing date 22.08.2024

Version number 43 (replaces version 42)

Revision: 22.08.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipa Heizkörper-Spray
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Color spray
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: MIPA SE
 Am Oberen Moos 1
 D-84051 Essenbach
 Tel.: +49 8703 92 20
 Fax.: +49 8703 92 21 00
 e-mail: sdb-registratur@mipa-paints.com
 www.mipa-paints.com
- · 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 STOT SE 3 H336 *Causes serious eye irritation. May cause drowsiness or dizziness.*

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation. • Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

Acetone

n-Butyl acetate

2-Methoxy-1-methylethyl acetate

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.



according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

Version number 43 (replaces version 42)

Trade name: Mipa Heizkörper-Spray

	(Contd. of page 1)
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
Additional inform	ation:
EUH066 Repeated	l exposure may cause skin dryness or cracking.
	Hazardous respirable droplets may be formed when sprayed. Do not breathe

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone	25-50%	
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226;	≤20%	
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21	Propane	10-25%	
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	Isobutane	2.5-<10%	
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31	Butane, pure	2.5-<10%	
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; (1) STOT SE 3, H336	<2.5%	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

GB



according to UK REACH

Revision: 22.08.2024

(Contd. of page 2)

Printing date 22.08.2024

Version number 43 (replaces version 42)

Trade name: Mipa Heizkörper-Spray

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:
- Do not seal receptacle gas tight. Keep container tightly sealed.
- Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)



Printing date 22.08.2024

Safety data sheet

according to UK REACH Version number 43 (replaces version 42)

Revision: 22.08.2024

Trade name: Mipa Heizkörper-Spray

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

67-64-1 Acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

106-97-8 Butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see section 7.

- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB



Safety data sheet according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

Version number 43 (replaces version 42)

Trade name: Mipa Heizkörper-Spray

(Contd. of page 4)



Tightly sealed goggles

9.1 Information on basic physical and	chemical properties
General Information	
Physical state	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point an	
boiling range	-44.5 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	1.2 Vol % (123-86-4 n-Butyl acetate)
Upper:	13 Vol % (67-64-1 Acetone)
Flash point:	<0 °C (DIN 53213)
Auto-ignition temperature:	365 °C (DIN 51794, 106-97-8 Butane, pure)
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (I	og
value)	Not determined.
Vapour pressure at 20 °C:	8,300 hPa (74-98-6 Propane)
Vapour pressure at 50 °C:	800 hPa
Density and/or relative density	
Density at 20 °C:	0.802 g/cm³ (DIN 53217)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection o	
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
	explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	80.26 %
Solids content (weight-%):	19.7 %
Change in condition	
Evaporation rate	Not applicable.



according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

Version number 43 (replaces version 42)

Trade name: Mipa Heizkörper-Spray

	(Contd. of page a
Information with regard to physical haz	ard
classes	
· Explosives	Void
[.] Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
[.] Gases under pressure	Void
· Flammable liquids	Void
Flammable solids	Void
[·] Self-reactive substances and mixtures	Void
[·] Pyrophoric liquids	Void
Pyrophoric solids	Void
• Self-heating substances and mixtures	Void
[•] Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
• Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
[·] Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

(Contd. on page 7)

GB



Printing date 22.08.2024

Safety data sheet

according to UK REACH

Revision: 22.08.2024

Version number 43 (replaces version 42)

Trade name: Mipa Heizkörper-Spray

(Contd. of page 6)

- 12.7 Other adverse effects
- · Additional ecological information:
- General notes:
- Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

 14.1 UN number or ID number ADR, IMDG, IATA 	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable
• 14.3 Transport hazard class(es) • ADR	
· Class · Label	2 5F Gases. 2.1
· IMDG, IATA	
· Class · Label	2.1 Gases. 2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
 14.5 Environmental hazards: Marine pollutant: 	No
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Code 	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE
	(Contd. on page 8)



according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

Version number 43 (replaces version 42)

Trade name: Mipa Heizkörper-Spray

UN "Model Regulation":	UN 1950 AEROSOLS, 2.1
IMDG Limited quantities (LQ)	1L
Tunnel restriction code	D
Transport category	2
Limited quantities (LQ)	1L
ADR	
Transport/Additional information:	
<i>14.7 Maritime transport in bulk according to IMO instruments</i>	Not applicable.
	For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
	For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.
	of 1 litre: Segregation as for class 9. Stow "separated fron class 1 except for division 1.4.
Segregation Code	AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacit
	(Contd. of page

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors
- None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 Acetone

Listed

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK 50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. (Contd. on page 9)



Safety data sheet according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

Version number 43 (replaces version 42)

Trade name: Mipa Heizkörper-Spray

		(Contd. of page 8)
· Releva	ant phrases	
H220		
H225		
H226	Flammable liquid and vapour.	
H280	Contains gas under pressure; may explode if heated.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
	66 Repeated exposure may cause skin dryness or cracking.	
	fication according to Regulation (EC) No 1272/2008	
	assification of the mixture is generally based on the calculation method using	substance data
	ling to Regulation (EC) No 1272/2008.	Substance uata
	viations and acronyms:	
	eglement international concernant le transport des marchandises dangereuses par chemin	de fer (Regulations
	ing the International Transport of Dangerous Goods by Rail)	de lei (Regulations
	nternational Civil Aviation Organisation	
ADR: Ac	ccord relatif au transport international des marchandises dangereuses par route (European Agi	eement Concerning
	national Carriage of Dangerous Goods by Road)	
	nternational Maritime Code for Dangerous Goods	
	ternational Air Transport Association Iobally Harmonised System of Classification and Labelling of Chemicals	
	European Inventory of Existing Commercial Chemical Substances	
	: European List of Notified Chemical Substances	
	nemical Abstracts Service (division of the American Chemical Society)	
	platile Organic Compounds (USA, EU)	
	ersistent, Bioaccumulative and Toxic	
	ery Persistent and very Bioaccumulative as 1A: Flammable gases – Category 1A	
	1: Aerosols – Category 1	
	Gas (Comp.): Gases under pressure – Compressed gas	
	Sas (Liq.): Gases under pressure – Liquefied gas	
	q. 2: Flammable liquids – Category 2	
	q. 3: Flammable liquids – Category 3	
	. 2: Serious eye damage/eye irritation – Category 2 E 3: Specific target organ toxicity (single exposure) – Category 3	
	compared to the previous version altered.	
Dala		GB -