

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 Version number 24 (replaces version 23)

Revision: 04.07.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipa Isoliergrund-Spray
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Priming
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: MIPA SE
 Am Oberen Moos 1
 D-84051 Essenbach
 Tel.: +49 8703 92 20
 Fax.: +49 8703 92 21 00
 e-mail: sdb-registratur@mipa-paints.com
 www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Aerosol 1	H222-H2	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
enviro	onment	
Aquatic Chroni	c 2 H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	H315	Causes skin irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word Danger

 Hazard-determining components of labelling: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics Kohlenwasserstoffe, 8-C9, Isoalkane

(Contd. on page 2)

GB



according to Regulation (EC) No 1907/2006, Article 31

Revision: 04.07.2024

Printing date 04.07.2024

07.2024 Version number 24 (replaces version 23)

Trade name: Mipa Isoliergrund-Spray

(Contd. of page 1) cyclohexane · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. P261 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national/international P501 regulations. · Additional information: EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Buildup of explosive mixtures possible without sufficient ventilation. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. vPvB: Not applicable. SECTION 3: Composition/information on ingredients · 3.2 Mixtures Description: Mixture of substances listed below with nonhazardous additions. Dangerous components: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, ≥10-<25% EC number: 921-024-6

Reg.nr.: 01-2119475514-35	<5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	Dimethyl ether أن Flam. Gas 1A, H220; Press. Gas (Liq.), H280	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-21194869440-21	Propane 🚸 Flam. Gas 1A, H220; Press. Gas (Liq.), H280	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31	Butane, pure 🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-25%
EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412, EUH066	≥10-<25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	Isobutane	2.5-<10%



according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.07.2024

Version number 24 (replaces version 23)

Revision: 04.07.2024

Trade name: Mipa Isoliergrund-Spray

EC number: 932-020-9	Kohlenwasserstoffe, 8-C9, Isoalkane	(Contd. of page 2 2.5-<10%
Reg.nr.: 01-2119548395-31	 ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; STOT SE 3, H336 	
CAS: 110-82-7	cyclohexane	<i>≥</i> 0.25-<2.5%
EINECS: 203-806-2 Reg.nr.: 01-2119463273-41	 Flam. Liq. 2, H225; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336 	
CAS: 110-54-3 EINECS: 203-777-6	n-hexane	<i>≥</i> 0.25-<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Seek immediate medical advice.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

• **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• **6.3 Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

(Contd. on page 4)

[–] GB

Professional Coating Systems

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Version number 24 (replaces version 23)

Revision: 04.07.2024

Trade name: Mipa Isoliergrund-Spray

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, *i.e. electric lights. Do not pierce or burn, even after use.*

7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 Dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

106-97-8 Butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

110-82-7 cyclohexane

WEL Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm

110-54-3 n-hexane

WEL Long-term value: 72 mg/m³, 20 ppm

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see section 7.

- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

(Contd. on page 5)



(Contd. of page 3)

GB



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Version number 24 (replaces version 23)

Revision: 04.07.2024

Trade name: Mipa Isoliergrund-Spray

(Contd. of page 4)

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Density at 20 °C:
 Relative density

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Not required.

SECTION 9: Physical and chemical properties · 9.1 Information on basic physical and chemical properties General Information • Physical state Aerosol · Colour: According to product specification Odour: Characteristic Odour threshold: Not determined. · Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling range -44.5 °C (74-98-6 Propane) · Flammability Not applicable. · Lower and upper explosion limit 1.5 Vol % (106-97-8 Butane, pure) · Lower: 18.6 Vol % (115-10-6 Dimethyl ether) · Upper: <0 °C (DIN EN ISO 1523:2002) · Flash point: • Auto-ignition temperature: 235 °C (DIN 51794, 115-10-6 Dimethyl ether) Not determined. · Decomposition temperature: · pH Not determined. · Viscosity: · Kinematic viscosity Not determined. · Dynamic: Not determined. · Solubilitv · water: Not miscible or difficult to mix. · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C: 8,300 hPa (74-98-6 Propane) Density and/or relative density

0.785 g/cm³ (DIN EN ISO 2811-1) Not determined.

(Contd. on page 6)

GB



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Version number 24 (replaces version 23)

Revision: 04.07.2024

Trade name: Mipa Isoliergrund-Spray

	(Contd. of page 5	
· Vapour density	Not determined.	
· 9.2 Other information		
· Appearance:		
· Form:	Aerosol	
· Important information on protection of hea	alth	
and environment, and on safety.		
· Ignition temperature:	Product is not selfigniting.	
· Explosive properties:	In use, may form flammable/explosive vapour-air	
	mixture.	
· Solvent content:		
· VOC (EC)	75.40 %	
· Solids content (weight-%):	24.6 %	
[.] Change in condition		
· Evaporation rate	Not applicable.	
· Information with regard to physical haz	ard	
classes		
· Explosives	Void	
· Flammable gases	Void	
Aerosols	Extremely flammable aerosol. Pressurised	
	container: May burst if heated.	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
• Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
• Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

 \cdot 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· Skin corrosion/irritation Causes skin irritation.

• STOT-single exposure May cause drowsiness or dizziness.

(Contd. on page 7)

GB



according to Regulation (EC) No 1907/2006, Article 31

Revision: 04.07.2024

Printing date 04.07.2024

Version number 24 (replaces version 23)

Trade name: Mipa Isoliergrund-Spray

- · Aspiration hazard May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN number or ID number		
· ADR, IMDG, IATA	UN1950	
• 14.2 UN proper shipping name		
ADR	UN1950 AEROSOLS	
·IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	
		(Contd. on page

(Contd. of page 6)



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 24 (replaces version 23)

Revision: 04.07.2024

Trade name: Mipa Isoliergrund-Spray

	(Contd. of page
14.3 Transport hazard class(es)	
ADR	
· Class	2 5F Gases.
	2.1
[.] Class	2.1 Gases.
· Label	2.1
IATA	
Class	2.1 Gases.
Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
· Marine pollutant: · Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler cod	
EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capaci of 1 litre: Category A. For AEROSOLS with
	capacity above 1 litre: Category B. For WAST
Sogragation Code	AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capaci
Segregation Code	of 1 litre:
	Segregation as for class 9. Stow "separated from
	class 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of
	class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision class 2.
14.7 Maritime transport in bulk according	
IMO instruments	Not applicable.



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Version number 24 (replaces version 23)

Revision: 04.07.2024

Trade name: Mipa Isoliergrund-Spray

	(Contd. of page 8)
· Transport/Additional information:	
 ADR Limited quantities (LQ) Transport category Tunnel restriction code 	1L 2 D
· IMDG · Limited quantities (LQ)	1L
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category
- P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %	
Ι	<1	
NK	50-100	

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.

(Contd. on page 10)



according to Regulation (EC) No 1907/2006, Article 31 Version number 24 (replaces version 23)

Revision: 04.07.2024

Printing date 04.07.2024

. .

Trade name: M	lipa Isolier	grund-Spray
---------------	--------------	-------------

(Contd. of page 9) H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Press. Gas (Liq.): Gases under pressure - Liquefied gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 ** Data compared to the previous version altered. GB