Revision: 22.01.2024



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.01.2024

Version number 14 (replaces version 13)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: Mipa EP 940-25 2K-EP-Härter
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

• 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms









GHS02 GHS05 GHS07 GHS09

· Signal word Danger

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Revision: 22.01.2024 Printing date 22.01.2024 Version number 14 (replaces version 13)

Trade name: Mipa EP 940-25 2K-EP-Härter

(Contd. of page 1)

Hazard-determining components of labelling:

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

Amines, polyethylenepoly-, triethylenetetramine fraction

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition P210

sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label). P321

P362+P364 Take off contaminated clothing and wash it before reuse.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 68082-29-1 NLP: 500-191-5 Reg.nr.: 01-2119972320-44	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1A, H317	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♠ Flam. Liq. 3, H226; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336, EUH066	5-<10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	2.5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene ♦ Flam. Liq. 2, H225; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H332	2.5-<10%
CAS: 90640-67-8 EINECS: 292-588-2 Reg.nr.: 01-2119487919-13	Amines, polyethylenepoly-, triethylenetetramine fraction Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.



according to 1907/2006/EC, Article 31

Printing date 22.01.2024 Version number 14 (replaces version 13) Revision: 22.01.2024

Trade name: Mipa EP 940-25 2K-EP-Härter

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 22.01.2024 Version number 14 (replaces version 13) Revision: 22.01.2024

Trade name: Mipa EP 940-25 2K-EP-Härter

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

107-98-2 1-methoxy-2-propanol

WEL | Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

Sk

100-41-4 Ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm

Sk

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 22.01.2024 Version number 14 (replaces version 13) Revision: 22.01.2024

Trade name: Mipa EP 940-25 2K-EP-Härter

(Contd. of page 4)

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

For the mixture of chemicals the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· **Physical state** Fluid

· Colour: According to product specification

· Odour: Characteristic
· Odour threshold: Not determined.

· Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 124-128 °C (123-86-4 n-Butyl acetate)

· Flammability Flammable.

· Lower and upper explosion limit

 Lower:
 1.1 Vol % (1330-20-7 Xylene)

 • Upper:
 7 Vol % (1330-20-7 Xylene)

 • Flash point:
 40 °C (DIN EN ISO 1523:2002)

*Auto-ignition temperature: 370 °C (DIN 51794, 123-86-4 n-Butyl acetate)

• **Decomposition temperature:** Not determined. • **pH** Not determined.

Viscosity:

• Kinematic viscosity at 20 °C 40 s (DIN 53211/4)
• Dvnamic: Not determined.

Solubility

water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Vapour pressure at 20 °C: 10.7 hPa (123-86-4 n-Butyl acetate)

· Vapour pressure at 50 °C: 55 hPa

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Revision: 22.01.2024 Printing date 22.01.2024 Version number 14 (replaces version 13)

Trade name: Mipa EP 940-25 2K-EP-Härter

(Contd. of page 5)

· Density and/or relative density

· Density at 20 °C: 0.921 g/cm3 (DIN EN ISO 2811-1)

· Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 49.95 % · Solids content (weight-%): 50.0 %

Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

· Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Void · Pyrophoric solids Self-heating substances and mixtures Void

Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 22.01.2024 Version number 14 (replaces version 13) Revision: 22.01.2024

Trade name: Mipa EP 940-25 2K-EP-Härter

(Contd. of page 6)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name		
ADR	UN1263 PAINT RELATED MATERIAL ENVIRONMENTALLY HAZARDOUS	
IMDG	PAINT RELATED MATERIAL (fatty acids, dimeres polymeres), MARINE POLLUTANT	
IATA	PAINT RELATED MATERIAL	
·IATA	PAINT RELATED MATERIAL	



according to 1907/2006/EC, Article 31

Printing date 22.01.2024 Version number 14 (replaces version 13) Revision: 22.01.2024

Trade name: Mipa EP 940-25 2K-EP-Härter

(Contd. of page 7) · 14.3 Transport hazard class(es) · ADR · Class 3 (F1) Flammable liquids. · Label · IMDG 3 Flammable liquids. · Class · Label 3 ·IATA · Class 3 Flammable liquids. · Label 3 · 14.4 Packing group · ADR, IMDG, IATA III· 14.5 Environmental hazards: Product contains environmentally hazardous substances: fatty acids, dimeres, polymeres No · Marine pollutant: Symbol (fish and tree) Symbol (fish and tree) · Special marking (ADR): · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 30 · EMS Number: F-E,<u>S-E</u> · Stowage Category · 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. · Transport/Additional information: · ADR Limited quantities (LQ) 5L 3 · Transport category Tunnel restriction code D/E · IMDG · Limited quantities (LQ) 5L · UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, III, **ENVIRONMENTALLY HAZARDOUS**



according to 1907/2006/EC, Article 31

Printing date 22.01.2024 Version number 14 (replaces version 13) Revision: 22.01.2024

Trade name: Mipa EP 940-25 2K-EP-Härter

(Contd. of page 8)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 22.01.2024 Version number 14 (replaces version 13) Revision: 22.01.2024

Trade name: Mipa EP 940-25 2K-EP-Härter

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

GB