

Printing date 11.01.2023

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 37 (replaces version 36)

Revision: 11.01.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipa PL 6 Ziehspachtel
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Knife filler/ Surfacer
- 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49(0)8703-922-0 Fax.: +49(0)8703-922-100 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com
- 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

health

health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation. **Hazard pictograms**



· Signal word Danger

• *Hazard-determining components of labelling:* Styrene maleic anhydride

(Contd. on page 2)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Revision: 11.01.2023

Printing date 11.01.2023

Version number 37 (replaces version 36)

Trade name: Mipa PL 6 Ziehspachtel

	(Contd. of page 1)
2,2'-(m-tolylimino)diethanol
Reaction mass of (4-methylphenyl)	f 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] amino]-
· Hazard statemer	nts
H226 Flammabl	e liquid and vapour.
H315 Causes sl	
H319 Causes se	erious eye irritation.
	e an allergic skin reaction.
•	d of damaging the unborn child.
	amage to the hearing organs through prolonged or repeated exposure.
· Precautionary s	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P35	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
P403+P235	Store in a well-ventilated place. Keep cool.
· 2.3 Other hazard	ls
· Results of PBT a	and vPvB assessment
DDT. Nat applias	blo.

- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 		
CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	Styrene Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	<i>≥</i> 10- <i>≤</i> 20%
CAS: 91-99-6 EINECS: 202-114-8	2,2'-(m-tolylimino)diethanol ♦ STOT RE 2, H373; ♦ Eye Dam. 1, H318; ↑ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1B, H317	<i>≥</i> 0.1-<1%
EC number: 911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino] bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]-	<i>≥</i> 0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	maleic anhydride	<i>≥</i> 0.001-<0.19



according to 1907/2006/EC, Article 31

Printing date 11.01.2023 Version number 37 (replaces version 36)

Revision: 11.01.2023

Trade name: Mipa PL 6 Ziehspachtel

(Contd. of page 2)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet • 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 4)

GB



Printing date 11.01.2023

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 11.01.2023

(Contd. of page 3)

Version number 37 (replaces version 36)

Trade name: Mipa PL 6 Ziehspachtel

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

100-42-5 Styrene

WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

108-31-6 maleic anhydride

WEL Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ Sen

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Revision: 11.01.2023

Printing date 11.01.2023

Version number 37 (replaces version 36)

Trade name: Mipa PL 6 Ziehspachtel

(Contd. of page 4)

· Breakthrough time of glove material

- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and che	mical properties
· General Information	
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
 Melting point/freezing point: 	Undetermined.
· Boiling point or initial boiling point and	
boiling range	145.2 °C (100-42-5 Styrene)
Flammability	Flammable.
Lower and upper explosion limit	
· Lower:	1.2 Vol %
· Upper:	8.9 Vol %
· Flash point:	34 °C (DIN 53213)
· Ignition temperature:	480 °C (DIN 51794)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	Not determined.
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	10,000 mPas
· Solubility	10,000 mil as
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log	Not determined.
value)	6 hPa
· Vapour pressure at 20 °C:	UTTA
 Density and/or relative density Density at 20 °C; 	$\frac{1}{2} \frac{604}{2} \frac{1}{2} $
Density at 20 °C:	1.624 g/cm ³ (DIN 53217)
Relative density	Not determined.
· Vapour density	Not determined.
[•] 9.2 Other information	
· Appearance:	
Form:	Fluid
· Important information on protection of he	
and environment, and on safety.	
• Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	1.07 %
· Solids content (weight-%):	83.8 %
	(Contd. on page 6)
	G



according to 1907/2006/EC, Article 31

Revision: 11.01.2023

Printing date 11.01.2023

3 Version number 37 (replaces version 36)

Trade name: Mipa PL 6 Ziehspachtel

		(Contd. of page
· Change in condition		
· Evaporation rate	Not determined.	
· Information with regard to physical haz	ard	
classes		
Explosives	Void	
· Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
[·] Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- \cdot 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- Reproductive toxicity Suspected of damaging the unborn child.
- STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

11.2 Information on other hazards

· Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

128-37-0 Butylated hydroxytoluene

(Contd. on page 7)

List II

List II



Printing date 11.01.2023

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 37 (replaces version 36)

Revision: 11.01.2023

Trade name: Mipa PL 6 Ziehspachtel

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

· **vPvB:** Not applicable.

· 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.


SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.





according to 1907/2006/EC, Article 31 Version number 37 (replaces version 36)

Revision: 11.01.2023

Printing date 11.01.2023

	(Contd. of page
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	<i>III</i>
· 14.5 Environmental hazards: · Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemle	er code): -
· EMS Number:	F-E,S-D
Stowage Category	A
· 14.7 Maritime transport in bulk acco	rding to
IMO instruments	Not applicable.
Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	E
·IMDG	
Limited quantities (LQ)	5L
UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

10-25

NK

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

[.] Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

(Contd. on page 9)

GB

Professional Goating Systems

Safety data sheet according to 1907/2006/EC, Article 31

according to 1907/2006/EC, Article 31 Version number 37 (replaces version 36)

Revision: 11.01.2023

Printing date 11.01.2023

Trade name: Mipa PL 6 Ziehspachtel

	((Contd. of page 8)
H332	Harmful if inhaled.	section of page of
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H361d		
H372	Causes damage to organs through prolonged or repeated exposure.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H412	Harmful to aquatic life with long lasting effects.	
	1 Corrosive to the respiratory tract.	
	fication according to Regulation (EC) No 1272/2008	
	ssification of the mixture is generally based on the calculation method using su	ıbstance data
accordir	ing to Regulation (EC) No 1272/2008.	
Abbrev	viations and acronyms:	
	glement international concernant le transport des marchandises dangereuses par chemin de	fer (Regulations
	ng the International Transport of Dangerous Goods by Rail)	
	ternational Civil Aviation Organisation	
	cord relatif au transport international des marchandises dangereuses par route (European Agreer	nent Concerning
	national Carriage of Dangerous Goods by Road)	
	ternational Maritime Code for Dangerous Goods ernational Air Transport Association	
	obally Harmonised System of Classification and Labelling of Chemicals	
	European Inventory of Existing Commercial Chemical Substances	
	European List of Notified Chemical Substances	
	emical Abstracts Service (division of the American Chemical Society)	
	latile Organic Compounds (USA, EU)	
	rsistent, Bioaccumulative and Toxic	
	ry Persistent and very Bioaccumulative	
	1. 3: Flammable liquids – Category 3	
	x. 4: Acute toxicity – Category 4	
	r. 1B: Skin corrosion/irritation – Category 1B 2: Skin corrosion/irritation – Category 2	
	2. Skill conosion/initiation – Category 2 n. 1: Serious eye damage/eye irritation – Category 1	
	2: Serious eye damage/eye irritation – Category 2	
	ens. 1: Respiratory sensitisation – Category 1	
Skin Sens	s. 1: Skin sensitisation – Category 1	
	s. 1A: Skin sensitisation – Category 1A	
	s. 1B: Skin sensitisation – Category 1B	
	Reproductive toxicity – Category 2	
STOT SE	3: Specific target organ toxicity (single exposure) – Category 3	
SIUIRE	 E 1: Specific target organ toxicity (repeated exposure) – Category 1 Specific target organ toxicity (repeated exposure) – Category 2 	
	E 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. 10X. Aquatic C	. 1: Aspiration hazard – Category 1 Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
	compared to the previous version altered.	
Dala	compared to the previous version altered.	05
		GB