

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 12 (replaces version 11)

Revision: 01.02.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipa PU 250-50 2K-PU-Lack
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- Sector of Use
- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Paint
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: MIPA SE
 Am Oberen Moos 1
 D-84051 Essenbach
 Tel.: +49(0)8703-922-0
 Fax.: +49(0)8703-922-100
 e-mail: sdb-registratur@mipa-paints.com
 www.mipa-paints.com
 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008



H226 Flammable liquid and vapour.



Flam. Liq. 3

Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



· Signal word Warning

 Hazard-determining components of labelling: n-Butyl acetate
 2-Methoxy-1-methylethyl acetate
 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
 Hydrocarbons, C9, aromatics

(Contd. on page 2)

⁻ GB



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 01.02.2023

Printing date 01.02.2023

Version number 12 (replaces version 11)

Trade name: Mipa PU 250-50 2K-PU-Lack

(Contd. of page 1) Hazard statements H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate � Flam. Liq. 3, H226; � STOT SE 3, H336, EUH066	<15%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	2.5-<10%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	2.5-<5%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335- H336, EUH066	1-<2.5%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of pentamethyl-piperidyl sebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; A Skin Sens. 1A, H317	<i>≥</i> 0.1-<0.25%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

GB

Professional Coating Systems

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 01.02.2023

(Contd. of page 2)

Printing date 01.02.2023

Version number 12 (replaces version 11)

Trade name: Mipa PU 250-50 2K-PU-Lack

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Use only in well ventilated areas. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection:* Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3

(Contd. on page 4)

----- GB



Safety data sheet

according to 1907/2006/EC, Article 31

Version number 12 (replaces version 11)

Revision: 01.02.2023

Trade name: Mipa PU 250-50 2K-PU-Lack

· 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

112-07-2 2-Butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
- · Respiratory protection:

Filter A/P2 (EN 141, EN 143)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: \geq 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

Value for the permeation: Level \leq 3

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB -



Safety data sheet according to 1907/2006/EC, Article 31

Version number 12 (replaces version 11)

Revision: 01.02.2023

(Contd. of page 4)

Trade name: Mipa PU 250-50 2K-PU-Lack

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

. 0.1 Information on basis physical and abomi	ical proportion
• 9.1 Information on basic physical and chemi • General Information	cal properties
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	404.400% (402.00 4 m Dutul contate)
boiling range	124-128 °C (123-86-4 n-Butyl acetate)
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	1.2 Vol %
· Upper:	7.5 Vol %
· Flash point:	30 °C (DIN 53213)
· Ignition temperature:	315 °C (DIN 51794)
 Decomposition temperature: 	Not determined.
рН	Not determined.
· Viscosity:	
 Kinematic viscosity at 20 °C 	190-200 s (ISO 6 mm)
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
· Vapour pressure at 20 °C:	<15 hPa
· Density and/or relative density	
· Density at 20 °C:	1.404 g/cm³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
· Appearance:	
· Form:	Fluid
 Important information on protection of healt 	h
and environment, and on safety.	
 Auto-ignition temperature: 	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
· Solvent content:	· · ·
· VOC (EC)	25.95 %
Solids content (weight-%):	74.1 %
Change in condition	
Evaporation rate	Not determined.
•	
 Information with regard to physical hazar 	u
classes	
· Explosives	Void
	(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 01.02.2023

Printing date 01.02.2023

Version number 12 (replaces version 11)

Trade name: Mipa PU 250-50 2K-PU-Lack

		(Contd. of page 5)
[.] Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
 Self-reactive substances and mixtures 	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
 Substances and mixtures, which emit 		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
• Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- **Thermal decomposition** / **conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards

· Endocrine disrupting properties

540-97-6	Dodecamethylcyclohexasiloxane	List II
541-02-6	Decamethylcyclopentasiloxane	List II
556-67-2	octamethylcyclotetrasiloxane	List II, III

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 7)

GB



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 12 (replaces version 11)

Revision: 01.02.2023

Trade name: Mipa PU 250-50 2K-PU-Lack

(Contd. of page 6)

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Remark: Harmful to fish

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

[.] Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263
 14.2 UN proper shipping name ADR IMDG, IATA 	UN1263 PAINT PAINT
· 14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
• 14.6 Special precautions for user	Warning: Flammable liquids.
 Hazard identification number (Kemler code): EMS Number: 	* 30 F-E,S-E
	(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 01.02.2023

Printing date 01.02.2023

Version number 12 (replaces version 11)

Trade name: Mipa PU 250-50 2K-PU-Lack

	(Contd. of page
Stowage Category	A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
Remarks:	≤ 450 l: 2.2.3.1.5 ADR
IMDG	
Limited quantities (LQ)	5L
Remarks:	≤ 30 l: 2.2.3.5 IMDG-Code
UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

• National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 9)



Safety data sheet

according to 1907/2006/EC, Article 31 Version number 12 (replaces version 11)

Revision: 01.02.2023

Trade name: Mipa PU 250-50 2K-PU-Lack

(Contd. of page 8) Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 * Data compared to the previous version altered. GB