

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 21 (replaces version 20)

Revision: 01.02.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Mipa PU 265-70 2K-PU-HS-Industry Chassislack**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MIPA SE  
Am Oberen Moos 1  
D-84051 Essenbach  
Tel.: +49(0)8703-922-0  
Fax.: +49(0)8703-922-100  
e-mail: sdb-registratur@mipa-paints.com  
www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Flam. Liq. 3      H226 Flammable liquid and vapour.



Aquatic Chronic 2    H411 Toxic to aquatic life with long lasting effects.



Skin Sens. 1      H317 May cause an allergic skin reaction.

STOT SE 3      H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02    GHS07    GHS09

- **Signal word** Warning
- **Hazard-determining components of labelling:**  
n-Butyl acetate  
2-Methoxy-1-methylethyl acetate  
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics  
Hydrocarbons, C9, aromatics

(Contd. on page 2)

**Trade name: Mipa PU 265-70 2K-PU-HS-Industry Chassislack**

(Contd. of page 1)

**Hazard statements**

- H226 Flammable liquid and vapour.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**

- PBT: Not applicable.
- vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients**
**3.2 Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	<15%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	2.5-<10%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	2.5-<5%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	1-<2.5%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	Trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<2.5%

(Contd. on page 3)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 21 (replaces version 20)

Revision: 01.02.2023

**Trade name: Mipa PU 265-70 2K-PU-HS-Industry Chassislack**

		(Contd. of page 2)
EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of pentamethyl-piperidyl sebacate ⚠ Repr. 2, H361f; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1A, H317	≥0.1-<0.25%
EC number: 939-607-9	Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates ⚠ Acute Tox. 3, H311; ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); ⚠ Acute Tox. 4, H302	≥0.025-<0.25%

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
 Supply fresh air and to be sure call for a doctor.  
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
 No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
 No further relevant information available.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
 CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
 No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
 Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
 Do not allow product to reach sewage system or any water course.  
 Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to item 13.  
 Ensure adequate ventilation.
- **6.4 Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.

(Contd. on page 4)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 21 (replaces version 20)

Revision: 01.02.2023

**Trade name: Mipa PU 265-70 2K-PU-HS-Industry Chassislack**

See Section 13 for disposal information.

(Contd. of page 3)

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.

· **Storage class:** 3

**7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**123-86-4 n-Butyl acetate**

WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm
	Long-term value: 724 mg/m <sup>3</sup> , 150 ppm

**108-65-6 2-Methoxy-1-methylethyl acetate**

WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 274 mg/m <sup>3</sup> , 50 ppm
	Sk

**112-07-2 2-Butoxyethyl acetate**

WEL	Short-term value: 332 mg/m <sup>3</sup> , 50 ppm
	Long-term value: 133 mg/m <sup>3</sup> , 20 ppm
	Sk

· **Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Hand protection**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 21 (replaces version 20)

Revision: 01.02.2023

**Trade name: Mipa PU 265-70 2K-PU-HS-Industry Chassislack**

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Breakthrough time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection**


Tightly sealed goggles

**SECTION 9: Physical and chemical properties**
**9.1 Information on basic physical and chemical properties**
**General Information**
**Physical state**

Fluid

**Colour:**

Different according to colouring

**Odour:**

Characteristic

**Odour threshold:**

Not determined.

**Melting point/freezing point:**

Undetermined.

**Boiling point or initial boiling point and boiling range**

124-128 °C (123-86-4 n-Butyl acetate)

**Flammability**

Flammable.

**Lower and upper explosion limit**
**Lower:**

1.2 Vol %

**Upper:**

7.5 Vol %

**Flash point:**

30 °C (DIN EN ISO 1523:2002)

**Ignition temperature:**

315 °C (DIN 51794)

**Decomposition temperature:**

Not determined.

**pH**

Not determined.

**Viscosity:**
**Kinematic viscosity at 20 °C**

315 s (DIN 53211/4)

**Dynamic:**

Not determined.

**Solubility**
**water:**

Not miscible or difficult to mix.

**Partition coefficient n-octanol/water (log value)**

Not determined.

**Vapour pressure at 20 °C:**

&lt;15 hPa

**Density and/or relative density**
**Density at 20 °C:**

 1.337 g/cm<sup>3</sup> (DIN EN ISO 2811-1)

**Relative density**

Not determined.

**Vapour density**

Not determined.

(Contd. on page 6)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 21 (replaces version 20)

Revision: 01.02.2023

**Trade name: Mipa PU 265-70 2K-PU-HS-Industry Chassislack**

(Contd. of page 5)

**· 9.2 Other information**
**· Appearance:**
**· Form:**

Liquid

**· Important information on protection of health and environment, and on safety.**
**· Auto-ignition temperature:**

Product is not selfigniting.

**· Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**· Solvent content:**
**· VOC (EC)**

29.14 %

**· Solids content (weight-%):**

70.9 %

**· Change in condition**
**· Evaporation rate**

Not determined.

**· Information with regard to physical hazard classes**
**· Explosives**

Void

**· Flammable gases**

Void

**· Aerosols**

Void

**· Oxidising gases**

Void

**· Gases under pressure**

Void

**· Flammable liquids**

Flammable liquid and vapour.

**· Flammable solids**

Void

**· Self-reactive substances and mixtures**

Void

**· Pyrophoric liquids**

Void

**· Pyrophoric solids**

Void

**· Self-heating substances and mixtures**

Void

**· Substances and mixtures, which emit flammable gases in contact with water**

Void

**· Oxidising liquids**

Void

**· Oxidising solids**

Void

**· Organic peroxides**

Void

**· Corrosive to metals**

Void

**· Desensitised explosives**

Void

**SECTION 10: Stability and reactivity**
**· 10.1 Reactivity** No further relevant information available.

**· 10.2 Chemical stability**
**· Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**· 10.3 Possibility of hazardous reactions** No dangerous reactions known.

**· 10.4 Conditions to avoid** No further relevant information available.

**· 10.5 Incompatible materials:** No further relevant information available.

**· 10.6 Hazardous decomposition products:** Carbon monoxide

**SECTION 11: Toxicological information**
**· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
**· Acute toxicity** Based on available data, the classification criteria are not met.

**· Respiratory or skin sensitisation** May cause an allergic skin reaction.

**· STOT-single exposure** May cause drowsiness or dizziness.

(Contd. on page 7)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 21 (replaces version 20)

Revision: 01.02.2023

**Trade name: Mipa PU 265-70 2K-PU-HS-Industry Chassislack**

(Contd. of page 6)

**11.2 Information on other hazards**
**Endocrine disrupting properties**

541-02-6	Decamethylcyclopentasiloxane	List II
556-67-2	octamethylcyclotetrasiloxane	List II, III
540-97-6	Dodecamethylcyclohexasiloxane	List II
78-93-3	Methyl ethyl ketone	List II

**SECTION 12: Ecological information**
**12.1 Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

**12.7 Other adverse effects**

- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**

Water hazard class 2 (German Regulation) : hazardous for water  
 Do not allow product to reach ground water, water course or sewage system.  
 Danger to drinking water if even small quantities leak into the ground.  
 Also poisonous for fish and plankton in water bodies.  
 Toxic for aquatic organisms

**SECTION 13: Disposal considerations**
**13.1 Waste treatment methods**
**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**
**14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN1263

**14.2 UN proper shipping name**

· **ADR** UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS  
 · **IMDG** PAINT (Solvent naphtha, Trizinc bis(orthophosphate)), MARINE POLLUTANT  
 · **IATA** PAINT

(Contd. on page 8)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 21 (replaces version 20)

Revision: 01.02.2023

**Trade name: Mipa PU 265-70 2K-PU-HS-Industry Chassislack**

(Contd. of page 7)

**· 14.3 Transport hazard class(es)**
**· ADR**


· **Class** 3 (F1) Flammable liquids.  
 · **Label** 3

**· IMDG**


· **Class** 3 Flammable liquids.  
 · **Label** 3

**· IATA**


· **Class** 3 Flammable liquids.  
 · **Label** 3

**· 14.4 Packing group**

· **ADR, IMDG, IATA** III

**· 14.5 Environmental hazards:**

Product contains environmentally hazardous substances: Trizinc bis(orthophosphate)

**· Marine pollutant:**

No  
 Symbol (fish and tree)

**· Special marking (ADR):**

Symbol (fish and tree)

**· 14.6 Special precautions for user**

Warning: Flammable liquids.

**· Hazard identification number (Kemler code):**

30

**· EMS Number:**

F-E, S-E

**· Stowage Category**

A

**· 14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

**· Transport/Additional information:**
**· ADR**

· **Limited quantities (LQ)** 5L

· **Transport category** 3

· **Tunnel restriction code** D/E

· **Remarks:** ≤ 5 l: 2.2.3.1.5 ADR

**· IMDG**

· **Limited quantities (LQ)** 5L

· **Remarks:** ≤ 5 l: 2.2.3.1.5 IMDG

**· UN "Model Regulation":**

UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

GB

(Contd. on page 9)



**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 21 (replaces version 20)

Revision: 01.02.2023

**Trade name: Mipa PU 265-70 2K-PU-HS-Industry Chassislack**

(Contd. of page 8)

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	25-50

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

**Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

*EUH066 Repeated exposure may cause skin dryness or cracking.*

**Classification according to Regulation (EC) No 1272/2008**

*The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.*

**Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
- ICAO: International Civil Aviation Organisation*
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: International Maritime Code for Dangerous Goods*
- IATA: International Air Transport Association*
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals*
- EINECS: European Inventory of Existing Commercial Chemical Substances*
- ELINCS: European List of Notified Chemical Substances*
- CAS: Chemical Abstracts Service (division of the American Chemical Society)*
- VOC: Volatile Organic Compounds (USA, EU)*
- PBT: Persistent, Bioaccumulative and Toxic*
- vPvB: very Persistent and very Bioaccumulative*
- Flam. Liq. 3: Flammable liquids – Category 3*

(Contd. on page 10)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2023

Version number 21 (replaces version 20)

Revision: 01.02.2023

**Trade name: Mipa PU 265-70 2K-PU-HS-Industry Chassislack**

(Contd. of page 9)

Acute Tox. 4: Acute toxicity – Category 4  
Acute Tox. 3: Acute toxicity – Category 3  
Skin Corr. 1C: Skin corrosion/irritation – Category 1C  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1  
Skin Sens. 1A: Skin sensitisation – Category 1A  
Repr. 2: Reproductive toxicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
· \* **Data compared to the previous version altered.**

GB