

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 2 (replaces version 1)

Revision: 25.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Mipa PU 850-10 2K-PU-Klarlack matt**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49 8703 92 20
Fax.: +49 8703 92 21 00
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 2 (replaces version 1)

Revision: 25.01.2024

Trade name: Mipa PU 850-10 2K-PU-Klarlack matt

(Contd. of page 1)

Hazard-determining components of labelling:

Xylene
 n-Butyl acetate
 2-Methoxy-1-methylethyl acetate
 Ethyl acetate

Hazard statements

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to the hearing organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3 Other hazards
Results of PBT and vPvB assessment

· **PBT:** Not applicable.
 · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients
3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	≤20%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	10-25%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	<15%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥10-<15%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 2 (replaces version 1)

Revision: 25.01.2024

Trade name: Mipa PU 850-10 2K-PU-Klarlack matt

(Contd. of page 2)

CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	Ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	2.5-<10%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336, EUH066	2.5-<5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	2.5-<10%
ELINCS: 400-830-7 Reg.nr.: 01-0000015075-76	Benzotriazole derivat ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1, H317	≥0.25-<1%
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of pentamethyl-piperidylsebacate ⚠ Repr. 2, H361f; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1A, H317	≥0.1-<0.25%
EC number: 939-607-9	Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyl-dimethyl, ethyl sulphates ⚠ Acute Tox. 3, H311; ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); ⚠ Acute Tox. 4, H302	≥0.025-<0.25%
CAS: 26761-45-5 EINECS: 247-979-2 Reg.nr.: 01-2119431597-33	2,3-Epoxypropyl neodecanoate ⚠ Muta. 2, H341; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Sens. 1, H317	≥0.1-<0.25%

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

 · **4.1 Description of first aid measures**

 · **General information:** Immediately remove any clothing soiled by the product.

 · **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

 · **After skin contact:** Immediately rinse with water.

 · **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

 · **After swallowing:** If symptoms persist consult doctor.

 · **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

 · **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

 · **5.1 Extinguishing media**

 · **Suitable extinguishing agents:**

 CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

 · **For safety reasons unsuitable extinguishing agents:** Water with full jet

 · **5.2 Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 2 (replaces version 1)

Revision: 25.01.2024

Trade name: Mipa PU 850-10 2K-PU-Klarlack matt

(Contd. of page 3)

- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-Butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m ³ , 150 ppm

108-65-6 2-Methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 2 (replaces version 1)

Revision: 25.01.2024

Trade name: Mipa PU 850-10 2K-PU-Klarlack matt

(Contd. of page 4)

112-07-2 2-Butoxyethyl acetate

WEL	Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk
-----	---

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

141-78-6 Ethyl acetate

WEL	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
-----	--

100-41-4 Ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
-----	---

· Ingredients with biological limit values:
1330-20-7 Xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 2 (replaces version 1)

Revision: 25.01.2024

Trade name: Mipa PU 850-10 2K-PU-Klarlack matt

(Contd. of page 5)

- **Breakthrough time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

- **General Information**
- **Physical state** Fluid
- **Colour:** According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** 77-78 °C (141-78-6 Ethyl acetate)
- **Flammability** Highly flammable.
- **Lower and upper explosion limit**
- **Lower:** 1.1 Vol % (1330-20-7 Xylene)
- **Upper:** 10.8 Vol % (108-65-6 2-Methoxy-1-methylethyl acetate)
- **Flash point:** -4 °C (DIN EN ISO 1523:2002, 141-78-6 Ethyl acetate)
- **Auto-ignition temperature:** 280 °C (DIN 51794, 112-07-2 2-Butoxyethyl acetate)
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity at 20 °C** 190-200 s (DIN 53211/4)
- **Dynamic:** Not determined.
- **Solubility**
- **water:** Not miscible or difficult to mix.
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure at 20 °C:** 97 hPa (141-78-6 Ethyl acetate)
- **Vapour pressure at 50 °C:** 360 hPa
- **Density and/or relative density**
- **Density at 20 °C:** 1.009 g/cm³ (DIN EN ISO 2811-1)
- **Relative density** Not determined.
- **Vapour density** Not determined.

· **9.2 Other information**

- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Solvent content:**
- **VOC (EC)** 63.51 %

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 2 (replaces version 1)

Revision: 25.01.2024

Trade name: Mipa PU 850-10 2K-PU-Klarlack matt

(Contd. of page 6)

· Solids content (weight-%):	36.5 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to the hearing organs through prolonged or repeated exposure.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 2 (replaces version 1)

Revision: 25.01.2024

Trade name: Mipa PU 850-10 2K-PU-Klarlack matt



(Contd. of page 7)

- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- | | |
|---|--------------------------------|
| · 14.1 UN number or ID number
· ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name
· ADR
· IMDG, IATA | UN1263 PAINT
PAINT |
| · 14.3 Transport hazard class(es)
· ADR | |
|  | |
| · Class
· Label | 3 (F1) Flammable liquids.
3 |
| · IMDG, IATA | |
|  | |
| · Class
· Label | 3 Flammable liquids.
3 |
| · 14.4 Packing group
· ADR, IMDG, IATA | II |

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 2 (replaces version 1)

Revision: 25.01.2024

Trade name: Mipa PU 850-10 2K-PU-Klarlack matt

(Contd. of page 8)

- | | |
|---|-----------------------------|
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| · Hazard identification number (Kemler code): | 33 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | B |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 5L |
| · Transport category | 2 |
| · Tunnel restriction code | D/E |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · UN "Model Regulation": | UN 1263 PAINT, 3, II |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

 · **Regulated explosives precursors**

None of the ingredients is listed.

 · **Regulated poisons**

None of the ingredients is listed.

 · **Reportable explosives precursors**

None of the ingredients is listed.

 · **Reportable poisons**

None of the ingredients is listed.

 · **Directive 2012/18/EU**

 · **Named dangerous substances - ANNEX I** None of the ingredients is listed.

 · **Seveso category P5c** FLAMMABLE LIQUIDS

 · **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

 · **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

 · **National regulations:**

 · **Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	50-100

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

 · **Relevant phrases**

H225 Highly flammable liquid and vapour.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 25.01.2024

Version number 2 (replaces version 1)

Revision: 25.01.2024

Trade name: Mipa PU 850-10 2K-PU-Klarlack matt

(Contd. of page 9)

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Muta. 2: Germ cell mutagenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**