

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Mipa VB 103-20 1K-PVB-Filler
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49 8703 92 20
Fax.: +49 8703 92 21 00
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Xylene
Propan-2-ol

Trade name: Mipa VB 103-20 1K-PVB-Filler

(Contd. of page 1)

Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100)

n-Butyl acetate

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|--|--|----------|
| CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25 | Propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 | 10-25% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32 | Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | ≥10-<15% |
| CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43 | Ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 % | 2.5-<10% |
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29 | n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066 | 5-<10% |
| CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46 | Ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 | 2.5-<10% |
| CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 | 2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336 | 2.5-<10% |
| CAS: 25068-38-6 | Bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight 700-1100) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 | 2.5-<10% |

(Contd. on page 3)

Safety data sheet

according to UK REACH

Printing date 22.08.2024

Version number 30 (replaces version 29)

Revision: 22.08.2024

Trade name: Mipa VB 103-20 1K-PVB-Filler

(Contd. of page 2)

| | | |
|---|--|----------|
| CAS: 9004-70-0 | Nitrocellulose, nitrogen content <12,6% ⚠ Expl. 1.1, H201 | 2.5-<10% |
| CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35 | Ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 | 2.5-<10% |
| CAS: 162627-17-0 EC number: 605-296-0 Reg.nr.: 01-2119970640-38 | Fatty acids, C18-unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine ⚠ Skin Sens. 1A, H317 | ≥0.1-<1% |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· 5.3 Advice for firefighters

· **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Trade name: Mipa VB 103-20 1K-PVB-Filler

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.
Information about storage in one common storage facility: Store away from foodstuffs.
Further information about storage conditions:
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

67-63-0 Propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

64-17-5 Ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

141-78-6 Ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm
Long-term value: 734 mg/m³, 200 ppm

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

100-41-4 Ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m³, 100 ppm
Sk

(Contd. on page 5)

Trade name: Mipa VB 103-20 1K-PVB-Filler

(Contd. of page 4)

Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

Filter A/P2 (EN 141, EN 143)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material Value for the permeation: Level ≤ 3

Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

According to product specification

(Contd. on page 6)

Safety data sheet

according to UK REACH

Printing date 22.08.2024

Version number 30 (replaces version 29)

Revision: 22.08.2024

Trade name: Mipa VB 103-20 1K-PVB-Filler

(Contd. of page 5)

| | |
|---|--|
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Undetermined. |
| · Boiling point or initial boiling point and boiling range | 78 °C (64-17-5 Ethanol) |
| · Flammability | Highly flammable. |
| · Lower and upper explosion limit | |
| · Lower: | 1.1 Vol % (1330-20-7 Xylene) |
| · Upper: | 12 Vol % (67-63-0 Propan-2-ol) |
| · Flash point: | 12 °C (DIN EN ISO 1523:2002) |
| · Auto-ignition temperature: | 370 °C (DIN 51794, 123-86-4 n-Butyl acetate) |
| · Decomposition temperature: | Not determined. |
| · pH | Not determined. |
| · Viscosity: | |
| · Kinematic viscosity at 20 °C | >60 s (ISO 6 mm) |
| · Dynamic: | Not determined. |
| · Solubility | |
| · water: | Not miscible or difficult to mix. |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure at 20 °C: | 97 hPa (141-78-6 Ethyl acetate) |
| · Density and/or relative density | |
| · Density at 20 °C: | 1.138 g/cm ³ (DIN EN ISO 2811-1) |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |

· 9.2 Other information

| | |
|--|---|
| · Appearance: | |
| · Form: | Fluid |
| · Important information on protection of health and environment, and on safety. | |
| · Ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Solvent content: | |
| · VOC (EC) | 52.06 % |
| · Solids content (weight-%): | 47.8 % |
| · Change in condition | |
| · Evaporation rate | Not determined. |

· Information with regard to physical hazard classes

| | |
|--|-------------------------------------|
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | Void |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Highly flammable liquid and vapour. |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |

(Contd. on page 7)

Trade name: Mipa VB 103-20 1K-PVB-Filler

(Contd. of page 6)

| | |
|----------------------------------|------|
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Possible in traces.
Nitrogen oxides
Hydrogen chloride (HCl)
Carbon monoxide
Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to the hearing organs through prolonged or repeated exposure.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

GB

(Contd. on page 8)

Safety data sheet

according to UK REACH

Printing date 22.08.2024

Version number 30 (replaces version 29)

Revision: 22.08.2024



Trade name: Mipa VB 103-20 1K-PVB-Filler

(Contd. of page 7)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

| | |
|---|-----------------------------|
| · 14.1 UN number or ID number | |
| · ADR, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name | |
| · ADR | UN1263 PAINT |
| · IMDG, IATA | PAINT |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 3 (F1) Flammable liquids. |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | II |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| · Hazard identification number (Kemler code): | 33 |
| · EMS Number: | F-E, S-E |
| · Stowage Category | B |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 5L |
| · Transport category | 2 |
| · Tunnel restriction code | D/E |

(Contd. on page 9)

Safety data sheet

according to UK REACH

Printing date 22.08.2024

Version number 30 (replaces version 29)

Revision: 22.08.2024

Trade name: Mipa VB 103-20 1K-PVB-Filler

(Contd. of page 8)

| | |
|----------------------------------|----------------------|
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · UN "Model Regulation": | UN 1263 PAINT, 3, II |

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Poisons Act**

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c FLAMMABLE LIQUIDS**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials, Annex II:**

| Class | Share in % |
|-------|------------|
| NK | 50-100 |

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H201 Explosive; mass explosion hazard.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 10)

Safety data sheet

according to UK REACH

Printing date 22.08.2024

Version number 30 (replaces version 29)

Revision: 22.08.2024

Trade name: Mipa VB 103-20 1K-PVB-Filler

(Contd. of page 9)

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

GB